

TECHNICAL DATA SHEET

PRODUCT: RETRACTABLE FALL ARRESTOR
REF. NO. : REG-RL- 2.5 TO 3.5

DOC. NO.	QF/RD/05
ISSUE	01
REVISION	00
DATE	25-04-2013



CONFORMING TO EN 360:2002

1	PHYSICAL PARAMETERS	General	<ul style="list-style-type: none"> • Robust and Durable Plastic Casing. • Has anchorage handle at anchorage end. • Steel swivel hook with load Indicator our ref. S-123 at the attachment end. • Galvanized steel wire rope (option of having S.S wire rope available)
2	LENGTH	<ul style="list-style-type: none"> • SRC-H- 2.5 Meters • SRC-H- 3.0 Meters • SRC-H- 3.5 Meters 	<ul style="list-style-type: none"> • 2.5 Meters • 3.0 Meters • 3.5 Meters
3	CABLE	<ul style="list-style-type: none"> • Material • Breaking strength 	<ul style="list-style-type: none"> • Galvanized steel wire rope \varnothing 4.5 (Min.) • 15 kN or 1,530 kgf (Min.)
4	WEIGHT	<ul style="list-style-type: none"> • SRC-H- 2.5 • SRC-H- 3.0 • SRC-H- 3.5 	<ul style="list-style-type: none"> • 2.120 kg • 2.160 kg • 2.200 kg
5	VITAL TEST COMPLIANCE	<ul style="list-style-type: none"> • Static strength • Dynamic performance 	<ul style="list-style-type: none"> • 13 kN or 1,325 kgf for 3 Min. • 100 kg mass free fall of 600 mm with the breaking force of less than 6 kN & arrest
6	LOCKING TEST	with 35 kg mass under conditioning to heat, cold & wet.	